


A ← LENS → B
LENS C = CENTER

5004917

DIMENSIONAL INFORMATION AND TERMS:

ALL DIMENSIONS ARE TO THE CENTER OF THE FIXTURE, UNLESS THE FIXTURE IS MOUNTED TO A DIMENSIONED SURFACE.

- TF - FIXTURE ROTATION TO THE FACE
- LR - FIXTURE ROTATION TO THE LEFT RIB
- RR - FIXTURE ROTATION TO THE RIGHT RIB
- TB - FIXTURE ROTATION TO THE BACK
- UP - FIXTURE ROTATION TO THE ROOF



- NOTES:
1. ALL FIXTURES WITH THE EXCEPTION OF HEAD LIGHTS ARE EQUIPPED WITH STEEL GUARDS.
 2. HEAD LIGHTS ARE PROTECTED BY 1/8" MIN. STEEL.
 3. THIS STE SHOWS THE MINIMUM LIGHTS REQUIRED. ADDITIONAL LIGHTS CAN BE ADDED TO MEET THE CUSTOMERS NEEDS.

MACHINE MODEL:

12 CM W/SCR

TOLERANCE:

MACHINE MODEL VARIATIONS ±6"
LIGHT PLACEMENT ±3" LINEAR
±5° ANGULAR
VOLTAGE AT FIXTURE ±5 %
OF RATED BULB VOLTAGE.

D	OPERATOR STA.	REMOTE CONTROL OPTIONAL				
C	CANOPY	CANOPY OPTIONAL WHEN USING REMOTE CONTROL OR IN COAL LESS THAN 42"				
6	27434-LP2		20	FL	+25"	RR
5	382	X/P1774-2	150	INC.	+25"	TB
4	382	X/P1774-2	150	INC.	+17"	TB
3	27434-LP2		20	FL	0"	LR
2	382	X/P1774-2	150	INC.	+3"	TB
1	382	X/P1774-2	150	INC.	0"	TB
ITEM	MODEL	X/P NO.	LAMP		LIGHT LOCATION FROM SURFACE -X- DIM ABOVE (+) DIM BELOW (-)	PACKING GLAND LOCATION
			WATTS	TYPE		

MINING CONTROLS INCORPORATED
P.O. BOX 1141 BECKLEY, WV 25802

DO NOT CHANGE WITHOUT "MSHA" APPROVAL

ENTRY SIZE
12' X 20'

DRAWN BY RAJ DATE DRAWN 5-7-92
APPROVED BY DATE APPROVED

TITLE
JOY MINER

DRAWING NUMBER 920415 REV. A